


# PROCITY



**BMC**

**CITY BUS SERIES**  
PROCITY (12 M LOW FLOOR)



### ENGINE

Brand/Model	Cummins ISB6,7 Euro VI
Type	Turbocharged Intercooler, Diesel
No of Cylinders	6
Stroke Volume	6,7 lt
Maximum Power	209 kW [280 HP] @ 2100 rpm
Maximum Torque	1100 Nm @ 1200 - 1600 rpm

### FUEL SYSTEM

Fuel Tank Capacity	250 lt
AdBlue Tank Capacity	38 lt

### TRANSMISSION

Brand/Model	ZF 6AP 1200B Ecolife, Automatic
Number of Gears	6 Forward - 1 Reverse

### AXLES

#### Front Axle

Brand/Model	ZF (Rigid)
Load Capacity	8.200 kg

#### Rear Axle

Diff. Brand/Model	ZF (Portal)
Gear Ratio	6.20:1
Load Capacity	13.000 kg

### STEERING

Type	Hydraulic
------	-----------

### BRAKES

Brake System Type	Air Controlled Disc (Front and Rear) EBS (ABS+ASR)
Retarder Type	Intarder, Activated via Hand Lever And/Or Brake Pedal

### SUSPENSION

Front Axle	Air Bellows (2), Hydraulic Absorbers (2)
Rear Axle	Air Bellows (4), Hydraulic Absorbers (4)
Kneeling	Side Kneeling (ECAS)
Anti-roll Bar	Rear Axle

### VEHICLE BODY

Body and Construction	Integral Design, Monocoque Chassis and Body, Low-floor
-----------------------	---

### TIRES/RIMS

Size	275/70 R22,5
Rims Size	8,25 x 22,5

### ELECTRICAL SYSTEM

Voltage	24 V Negative Ground
Batteries	2 X 12 V / 240 A

### DIMENSIONS (mm)

A: Wheelbase	5850
B: Vehicle Length	11970
C: Overall Width	2550
D: Maximum Height	3110
E: Inner Height	2370
F: Front Overhang	2840
G: Rear Overhang	3280
H: Front Track Width	2096
J: Rear Track Width	1832
K: Entrance Height	340
L: Inner Width	2410

### CAPACITY/AXLE LOADS

Passenger Capacity (Max.)	26 Seating + 77 Standing, 103 Total
Seating Capacity (Max.)	34 Seating (Incl. 4 Tip-up Seats)
Maximum Weight Loaded Front Axle	7100 kg
Maximum Weight Loaded Rear Axle	11500 kg
Gross Vehicle Weight	18000 kg

### STANDARD FEATURES

A/C 38 kW
Manuel Foldable Ramp
Automatic Fire Detection System
Electrically Controlled Heated Side Mirrors
Led Interior Lighting
Driver Cabin
Adjustable Steering Integrated with Cluster (DWP)
Digital Clock
LED Destination Panels

### OPTIONAL FEATURES

A/C with Roof Heating Function
Automatic Greasing System
Electrically Controlled Roof Hatch
LCD Monitor
Camera Surveillance System (with Recording)
Automatic Oil Filling
Driver A/C (Defroster)
Preheater
USB Charger
Tyre Pressure Monitoring System (TPMS)
Engine Room Automatic Fire Extinguishing System
Passenger Counting System
Announcement System
Rear View Camera and Display Screen
Tachograph (DTCO)
ESC (ESP)
Electric Fan for Ventilation
Independent Front Axle
300 HP Engine
2 x Double Doors Configuration (2-2-0)
Double Glazed Side Glasses

All visuals, dimensions, characteristics and equipments are for information purposes only and they are not contractual. BMC reserves the right to modify them without prior warning. (April 2019)

#### BMC Otomotiv Sanayi Ve Ticaret A.Ş.

**Headquarters** Oruç Reis Mah. Tem Otoyolu Atış Alanı Mevkii Tekstilkent Caddesi No: 12 Koza Plaza a Blok 4. Kat 34235 Esenler / İstanbul / Türkiye T. +(90 212) 438 04 30 F. +(90 212) 438 04 35

**Factory** Kemalpaşa Caddesi No: 288 Pınarbaşı 35060 Bornova / İzmir / Türkiye T. +(90 232) 477 18 00 F. +(90 232) 477 18 77 (78-79)

**Regional Directorate** Beştepe Mahallesi Dumlupınar Bulvarı No: 34 A Blok (Armada İş Merkezi) 6/1 Kat: 20 Yenimahalle / Ankara / Türkiye T. +(90 312) 285 91 25-26-27 F. +(90 312) 285 91 28