TGR 2532 (6x2) WBL ROAD TRUCK



BMC



CABIN

TVDF

Day Cab

CAB SUSPENSION

Mechanic

ENGINE

BRAND / MODEL

Cummins ISB6.7 (Euro 6)

TYPF

Turbo Intercooler Diesel

NUMBER OF CYLINDERS

DISPLACEMENT

6.7 L

MAXIMUM POWER

320 PS (239 kW) @ 2300 rpm

MAXIMUM TORQUE

1200 Nm @ 1100 rpm

DIAMETER & STROKE

107 mm / 124 mm

TANKS

FUEL TANK CAPACITY

500 L

ADBLUE TANK CAPACITY

GEAR BOX

BRAND / MODEL

ZF 9 S 1310 TD (Manual)

NUMBER OF GEARS

9 Forward, 1 Reverse

GEAR RATIO

12.73 - 1.00 (Reverse: 12.04)

CLUTCH

430 mm, Single Disc [S]

AXLES

FRONT AXLE

LOAD CAPACITY

7500 ka

REAR AXLE

Diff. Number of Speeds

Single Speed

Gear Ratio

4.33:1

LOAD CAPACITY

13000 kg

TAG AXLE

LOAD CAPACITY

9000 kg

SUSPENSION

FRONT AXLE

Semi-elliptical Springs, Telescopic Shock Absorbers

REAR AXLE

Compensating Mechanism Semi-elliptical Springs,

Telescopic Shock Absorbers

ANTI-ROLL BAR

Rear (2nd) and Front (1st) Axles

TYRES

SIZE / NUMBER

315 / 80 R 22.5, 10+1 [S]

315 / 70 R 22.5 , 6+1 [0] 315 / 60 R 22.5 , 6+1 [0]

DIMS

SIZE

9 x 22.5

PERFORMANCE

TOP SPEED (LIMITED) (km/h)

TURNING RADIUS (m)

ELECTRICAL SYSTEM

VOLTAGE

24 V

BATTERIES

2 x 12 V / 180 Ah

ALTERNATOR

120 A

STARTER MOTOR

STEERING SYSTEM

TYPE

Hydraulic

BRAKE SYSTEM

BRAKE SYSTEM TYPE

Air Operated Dual Circuit Type Disc Brakes,

EBS, ESC, AEBS, LDWS

RETARDER TYPE

Electromagnetic (475 kW)

ENGINE BRAKE

Engine Brake

CHASSIS

CHASSIS PROFILE

Steel, 8mm

STANDARD ACCESSORIES

Manually Operated Digital Air Conditioner (6 kW)

Radio/MP3/Bluetooth (1DIN)

2 USB + Cigarette Lighter (Driver Side)

2 USB + 12V (Passenger Side), 1 USB (Multimedia)

4 Points Independent Air Cab Suspension

Cruise Control

Electrically Operated and Heated Side Mirrors

Adjustable Steering Column

Mechanically Operated Sunroof

Electronic Brake System (EBS)

Electronic Stability Control (ESC)

Lane Departure Warning System (LDWS)

Immobilizer

Single Key with Remote Control and Central Locking

Differential Lock

Digital Tachograph

Electrically Operated Windows

Air Suspended Driver Seat

Adjustable Driver Seat Armrest

Seat Headrest

Seatbelt Sensor (Driver)

Driver and Passenger Sun Visor

Active Emergency Brake System (AEBS)

Spare Wheel

Front Fog Lamps

Electrically Operated Headlight Leveling

Lamp Under Hood Lamp Under Cab

Tyre Inflation Valve

, Body Structure Module

Pad Wear Indicator

1 (Driver) + 2 (Passenger) Seat Configuration

Hill-holder Assist

Tag Axle Lifting System

OPTIONAL ACCESSORIES

7" Multimedia Display

ADR Package

Retarder

Refrigerator (55lt) Driver Seat with Air Operated Back Support

Heated Driver Seat Adjustable Passenger Seat Armrest

Fleet Management System Socket and Module

Roof Spoiler


Tire Pressure Monitoring System

Electric Cab Lift Aluminum Rim

Transmission PTO

Front Dust Protection 315/60 Tyre Option 315/70 Tyre Option





DIMENSIONS (mm) A: Wheelbase 4250 H: Front Track B: Overall Length 9065 J: Rear Track C: Overall Width (Excluding Mirrors) 2545 S: First Step Height D: Overall Height 3300 R: Inner Width F: Useful Chassis Length 6921 K': Chassis Height P1: 2. and 3. Axle Distance I: Inner Height 1670

(Tunnel Height: 190)

1440

1915

*For kerb weight calculation, minimum equipment, no driver, 20 liters of fuel, 5 liters of urea included. Kerb weight may change depends on optional equipments Y247 2256 (Loaded)

[0] Options [3]. Standard

WEIGHTS (kg)

0: Front Overhang

G': Rear Overhang

TECHNICAL LEGAL MAXIMUM WEIGHT LOADED FRONT AXLE 7500 **GROSS VEHICLE WEIGHT** 25000

BMC OTOMOTIV SANAYI VE TİCARET A.Ş.

KERB WEIGHTS (kg) 4383

2083

1838

525

2155

1166

1350

1. AXLE 7500 2. AXLE 2078 MAXIMUM WEIGHT LOADED REAR AXLE 13000+9000 10500+7500 3 AXIF 1453 25000 TOTAL 7914*

All visuals, dimensions, characteristics and equipment are for information purposes only they are not contractual. BMC reserves the right to modify them without prior warning (February 2021).