TGR 3540 (6x4) TXT CONSTRUCTION TRUCK



BMC



CABIN

TYPF

Day Cab

CAB SUSPENSION

Mechanic

ENGINE

BRAND / MODEL

Cummins ISL9E6D (Euro 6)

TVDF

Turbo Intercooler Diesel

NUMBER OF CYLINDERS

DISPLACEMENT

891

MAXIMUM POWER

400 PS (298 kW) @ 2100 rpm

MAXIMUM TORQUE

1700 Nm @ 1400 rpm

DIAMETER & STROKE

114 mm / 145 mm

FUEL TANK CAPACITY

3001

ADBLUE TANK CAPACITY

GEAR BOX

BRAND / MODEL

ZF 16S1830 TO (Manual) [S] ZF 16S1831 TO (Manual+Intarder) [0]

NUMBER OF GEARS

16 Forward, 2 Reverse

GEAR RATIO

13.80:1; 0.84:1 (Reverse: 12.92:1 / 10.80:1)

CLUTCH

400 mm (15.5 ") Double Disc [S]

AXLES

FRONT AXLE LOAD CAPACITY

9000 kg

REAR AXLE

Gear Ratio

5 411

LOAD CAPACITY

16000 kg + 16000 kg

SUSPENSION

FRONT AXLE

Semi-elliptical Springs, Telescopic Shock Absorbers

REAR AXI E

Compensating Mechanism Semi-elliptical Springs,

Telescopic Shock Absorbers

ANTI-ROLL BAR

Rear (3rd) and Front (1st) Axles

TYPFS

SIZE / NUMBER

315 / 80 R 22.5, 10+1 [8] 13 R22.5, 10+1 [0]

RIMS

SIZE

9 x 22.5

PERFORMANCE

TOP SPEED (LIMITED) (km/h)

TURNING RADIUS (m)

ELECTRICAL SYSTEM

VOLTAGE

BATTERIES

2 x 12 V / 180 Ah

ALTERNATOR

120 A

STARTER MOTOR

24 V

STEERING SYSTEM

TYPF

Hydraulic

BRAKE SYSTEM

BRAKE SYSTEM TYPE

Air Operated Dual Circuit Type

Ø410x200 Z-Cam Disc Brakes, ABS, ASR

RETARDER TYPE

Intarder (600 kW) [0]

ENGINE BRAKE

252 kW [8]

CHASSIS

CHASSIS PROFILE

Steel, 8mm+5mm (Reinforced)

STANDARD ACCESSORIES

Manually Operated Digital Air Conditioner (6 kW)

Radio/MP3/Bluetooth (1DIN)

2 USB + Cigarette Lighter (Driver Side) 2 USB + 12V (Passenger Side), 1 USB (Multimedia)

4 Points Independent Mechanic Cab Suspension

Cruise Control

Electrically Operated and Heated Side Mirrors

Adjustable Steering Column

Manually Operated Sunroof

Antilock Braking System (ABS) Anti Slip Regulation (ASR)

Immobilizer

Single Kev with Remote Control and Central Locking

Differential Lock

Digital Tachograph

Electrically Operated Windows

Air Suspended Driver Seat

Adjustable Driver Seat Armrest

Seat Headrest

Seatbelt Sensor (Driver)

Driver and Passenger Sun Visor

Spare Wheel

Front Fog Lamps

Electrically Operated Headlight Leveling

Front Dust Protection Engine PTO - REPTO Lamp Under Hood

Lamp under Cab Tyre Inflation Valve Front Light protection

Body Structure Module

OPTIONAL ACCESSORIES

7" Multimedia Display

Driver Seat with Air Operated Back Support

Heated Driver Seat

Adjustable Passenger Seat Armrest [3]

Fleet Management System Socket and Module


Intarder (600 kW)

Electric Cab Lift

Tire Pressure Monitoring System

Signle Type Clutch System

Transmission PTO



DIMENSIONS (mm)

3900 B: Overall Length 7680 C: Overall Width (Excluding Mirrors) 2550

D: Overall Height 315/80/R 22,5: 3512 13R/22,5: 3544 F: Useful Chassis Length 5365

0: Front Overhana 1500 G': Rear Overhang 810

BMC OTOMOTİV SANAYİ VE TİCARET A.Ş.

A: Wheelbase

1670 (Tunnel Height: 190) H: Front Track J: Rear Track S: First Step Height

1847 315/80/R22,5: 553

R: Inner Width K': Chassis Height 13/R22,5:585 2155 315/80/R22,5: 1170

13R/22,5: 1203 P1: 2. and 3. Axle 1370

KERB WEIGHTS (kg)

WEIGHTS (kg)

I: Inner Height

MAXIMUM WEIGHT LOADED FRONT AXLE MAXIMUM WEIGHT LOADED REAR AXLE **GROSS VEHICLE WEIGHT**

TECHNICAL LEGAL 7000 8000 13400+13400 9500+9500 26000 34800

1. AXLE 2. AXLE 3 AXIF

5049 2405 2316 TOTAL 0770*

All visuals, dimensions, characteristics and equipment are for information purposes only they are not contractual. BMC reserves the right to modify them without prior warning (February 2021).